

Power Supply Module CS-VPP-xx-xx

CS-VPP-xx-xx is used with the **CaterSense®** -01-B and -01-DD controllers to increase the VA output on a controller from 15VA upto 40VA depending on the power pack selected.

The power pack comes in two sizes 10 and 25VA in either PCB format or mounted within an enclosure with a 5Amp neon rocker switch.

The 0v rail can be linked to Earth or let float.



Model Type	Model	Description
	CS-VPP-10-SW	10VA Power Pack Module with enclosure
	CS-VPP-25-SW	25VA Power Pack Module with enclosure
	CS-VPP-10-PCB	10VA Power Pack Module - PCB
Technical Data	Power supply (primary)	240Vac (fused)
	Power supply (secondary)	24Vac (fused)
	VA Rating	10 or 25
Wiring Terminals	L	240Vac Live
	N	Neutral
	E x 2	Earth
	24Vac x 2	Multi terminal 24Vac supply
	0v x 2	Multi terminal 0Vac supply
Damper or 3 Port Valve	B = 24V W = 0v G = Signal	
VeroVent or CaterSense	13 = Signal 14 = 0v	Controller connection
	J10	Link 0v to Earth Jumper



This symbol on this product or the package indicates that disposal of this product after its lifecycle could harm the environment.
DO NOT dispose of this product (or batteries if used) as unsorted municipal waste. It should be disposed by a specialised company for recycling.
This product should be returned to your distributor or to a local recycling service.
Respect the local environment rules.